

Performance Specs		SPS	RTX	PP-RTK	Post-Processed
Pos AV 210	PosiWon (m)	1.5 - 3.0	0.5 - 2.0	0.03 - 0.06	0.02 - 0.05
	Velocity (m/s)	0.05	0.05	0.02	0.015
	Roll & Pitch (deg)	0.04	0.03	0.03	0.025
	True Heading (deg)	0.30	0.28	0.18	0.08
Pos AV 310	PosiWon (m)	1.5 - 3.0	0.1 - 0.2	0.03 - 0.06	0.02 - 0.05
	Velocity (m/s)	0.05	0.05	0.010	0.010
	Roll & Pitch (deg)	0.03	0.02	0.015	0.015
	True Heading (deg)	0.10	0.08	0.035	0.035
Pos AV 510	PosiWon (m)	1.5 - 3.0	0.1 - 0.2	0.03 - 0.06	0.02 - 0.05
	Velocity (m/s)	0.05	0.05	0.005	0.005
	Roll & Pitch (deg)	0.008	0.008	0.005	0.005
	True Heading (deg)	0.070	0.040	0.008	0.008
Pos AV 610	PosiWon (m)	1.5 - 3.0	0.1 - 0.2	0.03 - 0.06	0.02 - 0.05
	Velocity (m/s)	0.030	0.030	0.005	0.005
	Roll & Pitch (deg)	0.005	0.005	0.0025	0.0025
	True Heading (deg)	0.030	0.020	0.005	0.005